



NüsingWall Eco 100

the simple movable wall solution.

Nüsing – movable wall technology



NüsingWall Eco 100

Sometimes less is simply more. Not really every space requires a partition wall solution with unlimited design possibilities and optional fittings. Only quality, functionality and easy-handling must always be highly valued – a requirement which we fulfill without compromise with our NüsingWall Eco 100.

Comfortable, quick and easy to operate, the NüsingWall Eco 100 offers tried and tested Nüsing brand quality:

- aluminium frame construction with functional height adjustment
- vertical aluminium profiles with integrated seals ensure strong inter-panel joints
- top and bottom sealing by aluminium pressure seals
- seal pressure 1800N

Convince yourself – the NüsingWall Eco 100 is our cost-efficient solution for your professional needs.

At a glance: product details compared with NüsingWall Premium 100.

- lighter aluminium frame construction
- maximum sound insulation value R_w , P 48 dB
- functional height adjustment mechanism
- seal pressure 1800 N
- only manual operation available
- no special finishes e.g. acoustic boards, mirrors, mouldings, glazing cut-outs possible
- no smoke or fire resistant versions available

Element types

One system, unlimited possibilities.

We offer you a complete dividing wall system with the following element varieties. All elements are divided symmetrically or according to the customer's request.



1.) Standard element



2.) Telescope element



3.) Corner element

Favourable price, uncompromising quality.

Panels: Standard panels, Telescope panels, Corner panels

Dimensions: Panel thickness: 100mm

Panel width: max. 1200mm

Panel height: max. 3000mm

Construction: Peripheral aluminium frame with height adjustment

Pressure seals: Extendable top and bottom aluminium seals with double seal profiles

Surfaces / Cladding: 10mm high quality chipboard, white laminated



Operating mechanism: Seals are operated manually by robust mechanism with the delivered crank handle

Inter-panel joints: Aluminium profile, natural anodized


Type EP (Exposed Profile): Vertical panel edges protected by aluminium profiles

Sound insulation: To BS EN ISO 140-3:1995 – up to Rw P 48 dB

Panel Stacking Options:



Track: Aluminium, white powder-coated finish, ceiling support angles in the same colour at no-extra cost



The Nüsing product range
offers you many possibilities:



Nüsing Premium 100 wall

- a movable wall with individual panels
- sound insulation up to R_w , P 59dB
- acoustic, smoke protection and fire protection versions available
- also available as Nüsing Eco wall



Nüsing Visioline glass wall

- glass movable wall with individual panels
- many different variations in décor (foil, paint, screen printing etc.)
- aluminium top and bottom profiles



Nüsing Faltina-wall

- solid double skin construction
- made-to-measure
- flat surface when closed
- sound insulation up to R_w , P 34 dB



Nüsing Flexi folding wall

- individual panels joined together by hinges
- access door standard
- glazed panels available
- sound insulation up to R_w , P 39dB

We reserve the right to make technical changes in line with our policy of continuous product improvement.



Franz Nüsing GmbH & Co. KG
Borkstraße 5
48163 Münster

Tel.: 0251 780010

Fax: 0251 7800127

0251 7800145

www.nuesing.com

info@nuesing.com